




# SAF BEARING LIMITED



skf SAF 22611 x 1.7/8 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 22611 x 1.7/8

SAF 22611 x 1.7/8 Bearing 2D drawings and 3D CAD models

$d_a$	47.625 mm
$D_a$	120 mm
$C_a$	52.807 mm
$A_1$	79.375 mm
$A_2$	123.825 mm
S	4.763 mm
$b_a$	36.513 mm
H	157.162 mm
$H_1$	82.55 mm
$H_2$	30.163 mm
J min.	206.375 mm
J max.	241.3 mm
L	279.4 mm
$N_1$	19.05 mm
$R_1$	44.45 mm
$R_2$	25.4 mm
$R_G$	1/4 NPT
$P_G$	1/8 NPT
h	36.513 mm
Housing	SAF 611
Stabilizing ring	SR-13-11
Labyrinth ring	2 x LER 23
End plug (suffix Y)	EPR 5
Bearing limiting speed	5600 r/min
$P_{60^\circ}$	43.1 kN



## SAF BEARING LIMITED

$P_{90^\circ}$	25.8 kN
$P_{120^\circ}$	16 kN
$P_{150^\circ}$	14.7 kN
$P_{180^\circ}$	17.8 kN
$P_a$	6.94 kN
Mass pillow block	13.7 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	68.04 g