



SAF BEARING LIMITED



skf FSAF 22615 x 2.1/2 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 22615 x 2.1/2

FSAF 22615 x 2.1/2 Bearing 2D drawings and 3D CAD models

d_a	63.5 mm
D_a	160 mm
C_a	64.795 mm
A_1	98.425 mm
A_2	149.225 mm
S	4.763 mm
b_a	44.45 mm
H	192.088 mm
H_1	101.6 mm
H_2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
J_1	53.975 mm
L	349.25 mm
N_1	19.05 mm
R_1	60.325 mm
R_2	27.94 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	40.481 mm
Housing	FSAF 615
Stabilizing ring	SR-18-15
Labyrinth ring	2 x LOR 38
End plug (suffix Y)	EPR 7
Bearing limiting speed	4300 r/min



SAF BEARING LIMITED

P_{60°	101 kN
P_{90°	60.9 kN
P_{120°	38.3 kN
P_{150°	34.7 kN
P_{180°	42.3 kN
P_a	12.5 kN
Mass pillow block	23.6 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	141.75 g